



Acrylic Bonding Liquid

Quart, Gallon and 5 Gallon



DAMTITE WATERPROOFING

733 E. Main Street
Monongahela, PA 15063-1499
1-800-223-8483
1-724-258-7175
Fax: 724-258-3188
e-mail: info@damtitewaterproofing.com
website: www.damtitewaterproofing.com

- **Additive to Damtite Powder Waterproofers**
- **Strengthens cement and plaster mixes**
- **Reduces cracking; improves bond**

Description:

A milky liquid that becomes clear when dry. Bonds new masonry materials to old; will assure adhesion of the Damtite coatings to previously painted surfaces, floors and non-porous surfaces when properly mixed; liquid portion of the Damtite Patch. Prevents separations, cracking and increases flexural strength. For exterior/interior use.

When using Damtite Waterproofer on previously painted or non-porous walls:

Replace 1/4-1/2 of water with **Damtite Bonding Liquid** to assure proper adhesion. Follow instructions on container. Normal ratio is 1 part Bonding Liquid to 3 parts clean water unless increased strength is required.

Bonding new concrete/stucco to old or resurfacing:

Thoroughly clean all surfaces. Apply a primer coat of **Damtite Bonding Liquid** with brush, roller, mop or sprayer within 1/2 hour prior to applying mix. Do not allow to harden; otherwise a reapplication is needed. Also, add Bonding Liquid to cement-based mix as noted above.

Mixing with cement grout:

Add two 100 lb. bags of clean washed sand to each 94 lb. bag of portland cement and mix thoroughly. Gradually add 5 gallons of **Damtite Bonding Liquid** while stirring. Do not add water unless mixture is too stiff to pour or trowel. To use with premixes such as "sand mix", determine the amount of cement in the dry mix and use 1 gallon of **Damtite Bonding Liquid** for each 20 lbs.

Size	Stock No.	Pack
Quart	05160	6
Gallon	05370	4
5 Gallon	05500	1

CAUTION:

KEEP OUT OF REACH OF CHILDREN.

Avoid prolonged contact with skin an breathing of vapor or spray mist. Use with adequate ventilation. **DO NOT TAKE INTERNALLY.** If swallowed, induce vomiting, **CONSULT A PHYSICIAN IMMEDIATELY.** For eye or skin contact, flush thoroughly with water. Close container after each use.

Dispose of unused liquid in accordance with local, state and federal requirements.

DAMTITE WATERPROOFING
 May 2010
Acrylic Bonding Liquid - Quart, Gallon & 5 Gallon