



**Latex Base, Ready Mixed
Masonry Waterproofer**

White - Gallon and 5 Gallon



DAMTITE WATERPROOFING

733 E. Main Street
Monongahela, PA 15063-1499
1-800-223-8483
1-724-258-7175
Fax: 724-258-3188
e-mail: info@damtitewaterproofing.com
website: www.damtitewaterproofing.com

FOR CONCRETE, BRICK & MASONRY

- **Stops water - guaranteed!**
- **Ecologically safe; low odor**
- **Tintable; easy clean-up**

EXCELLENT FOR:

- **basement walls**
- **garage walls**
- **exterior foundations
– above or below grade**
- **retaining walls**
- **stucco - brick - block**
- **poured concrete**
- **unventilated spaces**

Description:

A low-odor, high performance latex masonry waterproofer for interior and exterior, above or below grade applications. This tough, alkali-resistant coating provides excellent waterproofing protection with a decorative finish for all masonry, cinder & concrete block, poured concrete, brick, stucco, basement & retaining walls and foundations. No pre-mixing or pre-wetting is needed. Fast drying with easy soap & water cleanup. Conforms to and passed the performance requirements of TT-P-1411A & TT-C-555B. *NOT DESIGNED FOR USE ON FLOORS AND WILL NOT WITHSTAND FOOT TRAFFIC.*

Surface Preparation:

Most important step to insure maximum performance and adhesion. Clean the surface thoroughly, removing any loose mortar, paint, dirt, dust, grease, oil, form-release agents or frost. Remove any powdery, salt-like deposits (efflorescence) with **Damtite Concrete Cleaner**. For cracks or holes in the mortar joints, wall-floor joints, or in the concrete block, patch these areas with **Damtite Hydraulic Cement** and smooth the patch evenly to match the surrounding surface.

Application:

Stir thoroughly before using. **DO NOT THIN OR MIX WITH OTHER PAINTS.** Apply directly from the pail to dry (for best results) or slightly damp surface. Apply a generous coat, using a nylon-bristle brush. Work the paint into the surface making certain to fill all pores and voids. Allow the first coat to dry 12-24 hours before applying the second coat. **TWO COATS ARE REQUIRED FOR BEST WATERPROOFING PERFORMANCE.** Can use brush, roller or sprayer to apply second coat. For severe seepage areas, an additional coat may be required to fill pin holes and pores.

Coverage:

On rough, porous surfaces, up to 100 sq.ft./gal.; moderately porous surfaces, up to 125 sq. ft./gal.; smooth concrete or previously painted, up to 150 sq. ft./gal.

Tinting:

May be tinted to light shades with alkali-proof universal tinting colors. Use only 25% of color normally recommended. Do not use more than 2 fl. oz. of colorant per gallon. Colors may not exactly match tinting chart.

Drying Time:

Most surfaces will be dry to touch in 2-3 hours. Allow to dry 12-24 hours before applying the second coat.

Clean-Up/Storage/Disposal:

Clean hands and tools immediately after use with soap and warm water. Store unused product in

original container, in area above 40°F. Dispose of product in accordance with local, state and federal regulations.

Important:

- Best results when applied on dry, bare or untreated concrete and masonry surfaces. This product is not warranted when used over previously painted surfaces since it may prevent waterproofing performance.
- **Damtite Powder Waterproofer** is recommended for “ponding water” areas, such as concrete cisterns, fish ponds, or water tanks. If **Damtite Latex** is used on any enclosed areas, allow to dry at least 1 week prior to refilling. Increase ventilation to reduce drying time.
- Do not apply to frost covered or frozen walls, or in areas where surface temperature is expected to fall below 40° F within 48 hours.
- Do not use on floors, sandstone or glazed surface. Product will not withstand foot traffic.

LIMITED WARRANTY:

Damtite Waterproofing, Inc. warrants this product, when applied in accordance with directions on this label, on a properly prepared bare masonry surface will provide a waterproof coating for five (5) years from date of sale or Damtite will supply enough product to correct the condition or refund the purchase price of the product upon presentation of purchase receipt. Product failure due to incorrect product application, incorrect surface preparation, recurring efflorescence, structural damage, or conditions not reasonably foreseen by Damtite, are excluded. Any claim must be presented with original receipt to Damtite within five (5) years of sale date. This warranty does not include labor or the cost of labor for application nor any other damages.

CAUTION

KEEP OUT OF REACH OF CHILDREN.

Avoid contact with eyes and skin – may cause eye and skin irritation. Use with adequate ventilation during application and drying. Avoid breathing vapors and mist. If headaches, eye watering, nausea, or dizziness is experienced, move to a fresh air location or wear an approved respirator (NIOSH/MSHA TC 23C or equivalent). **Do not take internally.** Close lid after use. **FIRST AID: Eye Contact:** Flush thoroughly with water for at least 15 minutes. Notify a physician immediately. **Inhalation:** Move to an area of fresh air. If breathing difficulty continues, contact a physician for medical attention immediately. **Ingestion:** Drink two glasses of water, do not induce vomiting. Get immediate medical attention.

Coverage: 100-150 sq. ft. per gallon, depending upon surface

Size	Color	Stock No.	Pack
Gallon	White	03550	4
5 Gallon	White	03555	1

DAMTITE WATERPROOFING
 May 2010
Latex Base, Ready Mixed Masonry Waterproofer - White - Gal. & 5 Gal.